

The logo for the brand "Nice" is displayed in white text on a blue square background.

# SC-IC-SUB8

## Small Aperture Subwoofer



### *HIGH PERFORMANCE*

## 8.27" In-Ceiling Subwoofer with 4.75" Opening

The SC-IC-SUB8 high-performance small aperture in-ceiling subwoofer delivers best in class deep bass performance through a small, finished opening to meet the aesthetic needs of the modern home. Designed to hide the woofer cabinet between ceiling joists, and port the low frequency sound through a small 4.75" opening in the ceiling. It features a custom 8.27" polypropylene woofer, dual 1 1/2" voice coils, precision tuned port tube and a vinyl wrapped MDF cabinet, mounted to a single joist.

Designed and engineered in the USA in tandem with the SC-IC3 Small Aperture speaker and SC4-100 Amplifier to deliver three-way, full ranged sound in a complete system optimized for aesthetics, performance, and flexibility.



# SC-IC-SUB8 Small Aperture Subwoofer

## Features


- **8.27" Custom Polypropylene Cone**  
The cone size is maximized based on the cabinet proportions to deliver exceptional performance.
- **Dual Voice Coil**  
Easily integrate into existing stereo wiring, or use included shorting bars with a single amplifier channel.
- **Analog Filtering Circuits**  
Massive 10 MH Inductor for each voice coil, 1st-order filter, and CR circuit to suppress tube modes. Filters out unwanted frequencies to optimize woofer performance and reduce resonances resulting in deep clear bass.
- **4.75" Cut-out Size**  
Use a standard hole saw for a quick install into a broad range of materials
- **Simple Mounting**  
Mount cabinet to a single joist. Integrated absorption pads reduce kinetic transmission through the joist.




Includes two low-profile, paintable grilles for a round or square finish to match custom recessed lighting, fixtures and ceiling color.



(1) Round Low Profile Grille



(1) Square Low Profile Grille



Includes cut-out template for both grilles.  
*Optional Flush Mount Mudbank available for a near invisible aesthetic. (sold separately)*

## Specifications

Woofer Size	8.27"
Woofer Configuration	Fixed, Dual Voice Coil
Woofer Material	Polypropylene
Hole Cutout Dimensions	4.75"
Power Handling (Watts)	50 - Minimum / 100 - Maximum
Frequency Range	20Hz-300Hz
Impedance	8+8 Ohms
Sensitivity	71 dB
Weight	32 lbs
Dimensions	Cabinet: 25.188" (640mm) Length, 12" (305mm) Width, 7.125" (181mm) Depth Port Tube: 19" (483) Length, 3.25" (83mm) Diameter Sub Speaker Diameter: 5.25" (with Grille)
Shipping Dimensions	12" x 36" x 15" (302 x 907 x 874 mm)
Shipping Weight	34.4 lbs

### Accessories:

SC-IC3-PCB | Pre-Construction Bracket

SC-IC3-FLUSH-ROUND | Round Flush Mount Mudbank

SC-IC3-FLUSH-SQUARE | Square Flush Mount Mudbank



Niceforyou.com

©2023 Nice North America LLC. All rights reserved.  
Rev-B 07/2023