

EL-SC-100System Controller



Robust performance

The Nice EL-SC-100 System Controller offers robust performance at a price point that creates a new opportunities for smaller to moderate sized installations. The EL-SC-100 provides a single point of control and automation for media, climate, lighting, security, surveillance, and more.

Pair with the Nice EL-IO-200 as cost effective way of adding control connections to another area.

Where a universal remote would only provide access to media, lighting or climate, the EL-SC-100 enables intelligent integration of additional home systems that provide real value.

And with all control conducted via the award-winning Nice smart home management user interface, the EL-SC-100 delivers an exceptional experience.



EL-SC-100 System Controller



Features

Compatibility

Works with all current Nice user interfaces, including remotes, touch panels, and keypads, as well as iOS and Android mobile devices, and PC and Mac computers.

• Reliable

Ultra efficient fanless design with no moving parts delivers long lasting reliable operation.

Flexible

The compact design allows installation in cabinets, structured wiring cabinets, or behind a display.

Powerful

Easily automates small to moderate sized installations.

· A great partner

Extender mode enables use with ELAN® gSC series controllers on large installations.

• PoE or Wi-Fi connection

Allows for placement flexibility.

Specifications

RS-232	(1) RJ-45 Connector
Nice sense	(1) 3.5mm Connector
IR Output	(3) 3.5mm connectors (Mono), - 12V DC
Audio	(1) 3.5mm Connectors (Studio)
On-Screen Display	(1) HDMI Female Connector
USB	(1) USB A Connector
Ethernet	(1) RJ-45 PoE Connector
Wi-Fi	802.11 b/g/n
Software compatibility	Requires Core Module 8.4 or above
Updates	Managed by Core Module software
Power	Included Power Supply, 120/240VAC input 12VDC 1A output
Temperature	32°F to 131°F
Operating Humidity	90% Maximum (Non-Condensing)
Mounting	Free standing, Wall mount, Structured wiring cabinet
Product Dimensions	(in) 6 15/16W x 11/4H x 5D (mm) 176W x 31H x 126D
Product Weight	0.8 lb / 0.36 Kg
Certifications	CE, FCC, C-Tick
Warranty	2 Year





EL-SC-100-ZWSystem Controller with Z-Wave



Single point of control and automation

The Nice EL-SC-100 System Controller offers robust performance at a price point that creates a new opportunities for more smaller setups. For smaller moderate installations the EL-SC-100 provides a single point of control and automation for media, climate lighting, security surveillance and more. Pair with the EL-IO-200 as cost effective way of adding control connections to another area.

The Nice EL-SC-100 includes integrated Z-Wave, which eliminates the need to add third-party hardware (with optional EL-SC-ZW Z-Wave transceiver). Backed by and controlled through our award-winning Nice user interface, the EL-SC-100 delivers an exceptional experience.



EL-SC-100-ZW System Controller with Z-Wave



Features

Compatibility

Control all your devices, no matter what the format. Integrated IP, serial, and infrared control in a one-box design.

• Multi-Platform Experience

Themes and layouts will be consistent across all your devices, whether you're using the Nice Touch Panels or Mobile and Desktop Apps.

Compact

The design allows for installation in cabinets, structured wiring cabinets or behind a display.

PoE Ready

With Power over ethernet capability built in you can utilize your wired network setup to greatly reduce the amount of cables needed.

Z-WAVE Integration

Included Z-Wave functionality enables control and automation of compatible Z-Wave devices.

Network Flexibility

Connect these devices wired or wirelessly to the network for reliable control of all your devices; allowing for more installation flexibility.

· A great partner

Pair with the EL-IO-200 Control Extender or larger or decentralized installations.

Specifications

RS-232	(1) RJ-45 Connector
Nice sense	(1) 3.5mm Connector
IR Output	(3) 3.5mm connectors (Mono), - 12V DC
Audio	(1) 3.5mm Connectors (Studio)
On-Screen Display	(1) HDMI Female Connector
USB	(1) USB A Connector
Ethernet	(1) RJ-45 PoE Connector
Wi0Fi	802.11 b/g/n
Power	Coaxial Type A, 2.5mm inside diam.
Software compatibility	Requires Core Module 8.4 or above
Updates	Managed by Core Module software
Power	Included Power Supply, 120/240VAC input 12VDC 1A output
Temperature	32°F to 131°F
Operating Humidity	90% Maximum (Non-Condensing)
Mounting	Free standing, Wall mount, Structured wiring cabinet
Product Dimensions	6 15/16W x 1¼H x 5D (in) 176W x 31H x 126D (mm)

Product Weight	0.8 lb / 0.36 Kg
Certifications	CE, FCC, C-Tick
Warranty	2 Year
Z-Wave Transceiver	The state of the s
Frequency Band	868.4MHz - 916MHz
RZ-Wave	700 series
Supported Regions	Multi-Region
Connection	USB / Nice Controller
Power Consumption	5V
Operating Temperature	32 to 104f / 0 to 40C
Operating Humidity	90% Maximum (Non-Condensing)
Product Dimensions	1.5w x 1.5H x .5D (in) /40W x 40W x 17D (mm)
Connector Cable Length	6.5 ft / 2m

